

UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION N	Ю.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/620,880		07/16/2003	Kazuhisa Senda	121036-055	9102
35684	7590	10/21/2004		EXAMINER	
BUTZEL LONG				MITCHELL, KATHERINE W	
350 SOUTH MAIN STREET SUITE 300			ART UNIT	PAPER NUMBER	
ANN ARBOR, MI 48104		1I 48104		3677	
				DATE MAILED: 10/21/200-	4

Please find below and/or attached an Office communication concerning this application or proceeding.

	Application No.	Applicant(s)					
Office Action Commence	10/620,880	SENDA ET AL.					
Office Action Summary	Examiner	Art Unit	$\overline{\ \ }$				
	Katherine W Mitchell	3677	, 				
The MAILING DATE of this communicat Period for Reply	ion appears on the cover sheet with	he correspondence address					
A SHORTENED STATUTORY PERIOD FOR THE MAILING DATE OF THIS COMMUNICA - Extensions of time may be available under the provisions of 37 after SIX (6) MONTHS from the mailing date of this communic: - If the period for reply specified above is less than thirty (30) da - If NO period for reply is specified above, the maximum statutor - Failure to reply within the set or extended period, for reply will, in Any reply received by the Office later than three months after the earned patent term adjustment. See 37 CFR 1.704(b).	TION. CFR 1.136(a). In no event, however, may a reply ation. ys, a reply within the statutory minimum of thirty (3 y period will apply and will expire SIX (6) MONTH; by statute, cause the application to become ABAN	be timely filed O) days will be considered timely. Form the mailing date of this communication. DONED (35 U.S.C. § 133).					
Status							
1) Responsive to communication(s) filed o	n <i>16 July 200</i> 3.						
	This action is non-final.						
	Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under <i>Ex parte Quayle</i> , 1935 C.D. 11, 453 O.G. 213.						
Disposition of Claims							
4) ☐ Claim(s) 1-9 and 21 is/are pending in the 4a) Of the above claim(s) is/are with 5) ☐ Claim(s) is/are allowed. 6) ☐ Claim(s) 1-9 and 21 is/are rejected. 7) ☐ Claim(s) is/are objected to. 8) ☐ Claim(s) are subject to restriction.	vithdrawn from consideration.						
Application Papers							
9) The specification is objected to by the Ex	kaminer.						
10)⊠ The drawing(s) filed on <u>16 July 2003</u> is/a	, , , ,	•					
Applicant may not request that any objection	÷ , ,	, ,					
Replacement drawing sheet(s) including the 11) The oath or declaration is objected to by		. ,					
Priority under 35 U.S.C. § 119							
12) Acknowledgment is made of a claim for the a) All b) Some * c) None of: 1. Certified copies of the priority doces. 2. Certified copies of the priority doces. 3. Copies of the certified copies of the application from the International. * See the attached detailed Office action for	numents have been received. Numents have been received in App ne priority documents have been re Bureau (PCT Rule 17.2(a)).	ication No ceived in this National Stage					
Attachment(s)							
 Notice of References Cited (PTO-892) Notice of Draftsperson's Patent Drawing Review (PTO-5 		mary (PTO-413) ail Date					
3) Information Disclosure Statement(s) (PTO-1449 or PTO Paper No(s)/Mail Date		mal Patent Application (PTO-152)					

Ápplication/Control Number: 10/620,880 Page 2

Art Unit: 3677

DETAILED ACTION

Election/Restrictions

1. Applicant is correct that the Preliminary Amendment eliminated the restriction requirement. The preliminary amendment filed 7/16/03 is being used in the examination of this application.

Information Disclosure Statement

2. The IDS is presently unavailable to examiner. It will be reviewed as soon as it becomes available. If any citation on the IDS is used in a rejection of a pending claim, not due to amendment, such office action will be non-final.

Specification

3. The abstract of the disclosure is objected to because it does not describe the pending invention. The parent case claimed the inverted T-type stepped wall cross section shaped gasket; however, this divisional application has no claims regarding this feature. Applicant is correct in filing the exact same specification, including abstract, for a divisional application, but at this point the abstract should be amended to reflect the pending claims. Correction is required. See MPEP § 608.01(b).

Claim Rejections - 35 USC § 112

- 4. The following is a quotation of the second paragraph of 35 U.S.C. 112:
 The specification shall conclude with one or more claims particularly pointing out and distinctly claiming the subject matter which the applicant regards as his invention.
- 5. Claims 6-7 are rejected under 35 U.S.C. 112, second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter

Art Unit: 3677

which applicant regards as the invention. The claims disclose a hardness value with no units. Values without units are vague and ambiguous.

Claim Rejections - 35 USC § 103

- 6. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
 - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 7. Claims 21 and 2-5 and 8-9 are rejected under 35 U.S.C. 103(a) as being unpatentable over Tsurutani et al USP 6284403,hereafter called US403 in view of Kuse Katsuro JP 10-95071, hereafter called JP95071.

Re claims 21 and 3-5 and 8-9: US403 teaches a gasket for sealing fluids of a fuel cell. Fig 7 shows the mold, and col 7 lines 19-44 teach the method of producing the gasket in more detail, including providing a mold, providing a resin film (53) in the mold and molding a gasket body (51) on said resin film. Col 7 lines 33-36 teach that the film and gasket layer are joined by adhesive, heat welding, or the injection molding process itself. Batteries inevitably have an electrolyte solution which would contact the gasket, as also described in col 8 lines 31-41. However, US403 does not disclose that the rubber layer comprise an addition reaction type silicone rubber. JP95071 teaches that silicone rubber has outstanding heat resistance and cushioning properties in paragraph [0002], and paragraphs [0008-0010] teach an additive type silicone rubber. Excellent cushioning properties inevitably provide excellent compressibility for gaskets.

Art Unit: 3677

JP95071 also teaches in paragraphs [0038-0040] the importance of the adhesive and film with the silicone rubber. Therefore, it would have been obvious to one of ordinary skill in the art, having the teachings of US403 and JP95071 before him at the time the invention was made, to modify US403 as taught by JP95071 to include using an additive silicone rubber as the rubber component of the gasket as taught by JP95071, in order to obtain a heat resistant and compressible, flexible gasket that thus provides excellent sealing properties when combined with a resin film for strength. One would have been motivated to make such a combination because a gasket with high strength, good heat resistance, excellent resilience and compressibility, and relatively low cost would have been obtained, as taught/suggested by JP95071.

Further Re claims 2-5: Paragraph [0010 specifies the viscosity of the silicone rubber, and the fact that it can be formed in a mold requires it to be a liquid or paste. Paragraph [0044] teaches a polyester film .038 mm, or 38 micrometers thick and paragraph [0051] teaches film 35 micrometers thick.

8. Claims 6 and 7 are rejected under 35 U.S.C. 103(a) as being unpatentable over US403 in view of JP95071 as applied above and further in view of Oshima et al USP 5704803, hereafter called US 803. As discussed above, US403 in view of JP95071 teach all the elements except the desired rubber hardness. US803 teaches in col 3 lines 56-60 that silicone rubber with a Shore A hardness of 10-70 is used as a battery gasket. Therefore, it would have been obvious to one of ordinary skill in the art, having the teachings of US403 and JP95071 as applied to claim 3 above and US803 before him at the time the invention was

Art Unit: 3677

made, to modify US403 and JP95071 as applied to claim 3 to further include a Shore A hardness under 70 as taught by US803, in order to obtain compressible, flexible gasket that thus provides excellent sealing properties when combined with a resin film for strength. One would have been motivated to make such a combination because a lower hardness numbers indicate higher compressibility and better sealing.

9. Claims 21 and 2-5 and 8-9 are rejected under 35 U.S.C. 103(a) as being unpatentable over Tsurutani et al USP 6284403, hereafter called US403 in view of Hiroshi JP 8-148391, hereafter called JP148391.

Re claims 21 and 2-5 and 8-9: US403 teaches a gasket for sealing fluids of a fuel cell. Fig 7 shows the mold, and col 7 lines 19-44 teach the method of producing the gasket in more detail, including providing a mold, providing a resin film (53) in the mold and molding a gasket body (51) on said resin film. Col 7 lines 33-36 teach that the film and gasket layer are joined by adhesive, heat welding, or the injection molding process itself. Batteries inevitably have an electrolyte solution which would contact the gasket, as also described in col 8 lines 31-41. However, US403 does not disclose that the rubber layer comprise an addition reaction type silicone rubber. JP148391 teaches that silicone rubber has outstanding heat resistance and cushioning properties in paragraph [0038-0039], which teach an additive type silicone rubber for improved adhesion. Excellent cushioning properties inevitably provide excellent compressibility for gaskets. JP148391 also teaches in paragraphs [0038-0039] the importance of a nylon film and adherence of the silicone rubber to the nylon film. Therefore, it

Art Unit: 3677

would have been obvious to one of ordinary skill in the art, having the teachings of US403 and JP148391 before him at the time the invention was made, to modify US403 as taught by JP148391 to include using an additive silicone rubber as the rubber component of the gasket as taught by JP148391, in order to obtain a heat resistant and compressible, flexible gasket that thus provides excellent sealing properties when combined with a resin film for strength. One would have been motivated to make such a combination because a gasket with high strength, good heat resistance, excellent resilience and compressibility, and relatively low cost would have been obtained, as taught/suggested by JP148391.

Further Re claims 2-5: JP148391 teaches a film thickness of preferably 10-80 micrometers in [0020]. Since the silicone rubber is molded and mixed with peroxide, it is inevitably a liquid or paste.

10. Claims 6 and 7 are rejected under 35 U.S.C. 103(a) as being unpatentable over US403 in view of JP148391 as applied above and further in view of Oshima et al USP 5704803, hereafter called US 803. As discussed above, US403 in view of JP148391 teach all the elements except the desired rubber hardness. US803 teaches in col 3 lines 56-60 that silicone rubber with a Shore A hardness of 10-70 is used as a battery gasket. Therefore, it would have been obvious to one of ordinary skill in the art, having the teachings of US403 and JP148391 as applied to claim 3 above and US803 before him at the time the invention was made, to modify US403 and JP148391 as applied to claim 3 to further include a Shore A hardness under 70 as taught by US803, in order to obtain compressible, flexible gasket that thus provides excellent sealing properties when combined

Art Unit: 3677

with a resin film for strength. One would have been motivated to make such a combination because a lower hardness numbers indicate higher compressibility and better sealing.

Conclusion

- 11. The prior art made of record and not relied upon is considered pertinent to applicant's disclosure.
- 12. Any inquiry concerning this communication or earlier communications from the examiner should be directed to Katherine W Mitchell whose telephone number is 703-305-6713. The examiner can normally be reached on Mon Thurs 10 AM 8 PM.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, J. J. Swann can be reached on 703-306-4115. The fax phone number for the organization where this application or proceeding is assigned is 703-872-9306.

13. Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

Katherine W Mitchell Patent Examiner Art Unit 3677

Kwm 10/17/2004

> ROBERT L SANDY RIMARY EXAMINER